



## CONNECTION FOR CENTRAL EXTRACTION

Duct connection outlet is designed in the right diameter for central dust extraction system

## EXPANDABLE WORKING AREA

Openable side panels allow you to expand working area. 3 Position is available

## INTEGRATED SPARK SHIELD

Integrated spark shield protect main dust collector from sparks which could be avvarise during grinding operation

## GRID PANELS FOR EASY MAINTENANCE

Grid base panels can be remove easily with hand and allow you to clean hooper easily.

## HIGH QUALITY STEEL STRUCTURE

High quality and durable steel structure is designed and manufactured to operated in the most harsh environments.

GENERAL INFORMATION	
Type	Bench for Fume Extraction
Application	Fume (Welding etc.)

ORDER NO	
Welding Bench for Extraction	BKM.80.120

\*BKM series benches are modular. So you can place them side by side and increase working zone. If you want custom working zone, please do not hesitate to contact with Bomaksan Sales Team.

TECHNICAL INFORMATION	
Rec. Air Flow	min. 2.200 m <sup>3</sup> /h
Outlet Diameter	200 mm
Dimension (W x L x H)	1.200 x 885 x 1.550 mm
Bench Height	870 mm

\*BKM series need to be equipped with a dust collection system. They do not have integrated extraction fan and filters.

## PRESSURE LOSS

