



### EXPANDABLE WORKING AREA

Openable side panels allow you to expand working area. 3 Position is available

### INTEGRATED SPARK SHIELD

Integrated spark shield protect main dust collector from sparks which could be arise during grinding operation

### GRID PANELS FOR EASY MAINTENANCE

Grid base panels can be remove easily with hand and allow you to clean hooper easily.

### HIGH QUALITY STEEL STRUCTURE

High quality and durable steel structure is designed and manufactured to operated in the most harsh environments.

### CONNECTION FOR CENTRAL EXTRACTION

Duct connection outlet is designed in the right diameter for central dust extraction system

GENERAL INFORMATION	
Type	Bench for Dust Extraction
Application	Dust (Grinding etc.)

ORDER NO	
Standard Working Zone (80 x 120 cm)	BTM.80.120

\*BTM series benches are modular. So you can place them side by side and increase working zone. If you want custom working zone, please do not hesitate to contact with Bomaksan Sales Team.

TECHNICAL INFORMATION	
Rec. Air Flow	min. 2.200 m <sup>3</sup> /h
Outlet Diameter	200 mm
Dimension (W x L x H)	1.200 x 885 x 1.525 mm
Bench Height	870 mm

\*BTM series need to be equipped with a dust collection system. They do not have integrated extraction fan and filters.

### PRESSURE LOSS

