



CLEANABLE CARTRIDGE FILTERS

Top quality and cleanable cartridge filters allow you long filter lifetime and lower cost of ownership

EXPANDABLE WORKING AREA

Openable side panels allow you to expand working area. 3 Position is available

INTEGRATED SPARK SHIELD

Integrated spark shield protect main dust collector from sparks which could be arise during grinding operation

INTEGRATED RADIAL FAN

High efficient and silent radial fan provides high extraction efficiency

TRAY FOR WASTE DUST

Tray for easy discharge of waste dust

| GENERAL INFORMATION | |
|-------------------------|-------------------|
| Filter Type | Cartridge |
| Filter Media | |
| Standard | nanoBLEND FR |
| Optional | polyMIGHT PTFE 65 |
| No of Cartridge Filters | 2 |
| Total Filtration Area | |
| Standard | 40 m ² |
| Optional | 20 m ² |
| Filtration Efficiency | |
| Standard | F9 Class |
| Optional | H13/H14 Class |

| TECHNICAL INFORMATION | |
|------------------------|--------------------------|
| Extraction Capacity | |
| Standard | 2.500 m ³ /h |
| PRO version | 5.500 m ³ /h |
| Dimensions (W x L x H) | 1.300 x 1.100 x 1.450 mm |
| Motor Power | |
| Standard | 1,5 kW - 1.500 rpm |
| PRO version | 4,0 kW - 3.000 rpm |
| Power Supply | 380 V / 50 Hz |
| Noise Level | 75 dB(a) |

| ORDER NO | |
|-----------------------|------------------------------------|
| Standard Version, SFS | TBENCH.80.120.40.B135FR.380.50 |
| Standard Version, OFS | TBENCH.80.120.20.265PTFE.380.50 |
| PRO Version, SFS | TBENCHPRO.80.120.40.B135FR.380.50 |
| PRO Version, OFS | TBENCHPRO.80.120.20.265PTFE.380.50 |

SFS : Standard Filter Set
OFS: Optional Filter Set

| SPARE PART ORDER NO | |
|--------------------------|----------------------------|
| nanoBLEND FR Filter | HTM/450/450/500/B135FR/20 |
| polyMIGHT PTFE 65 Filter | HTM/450/450/500/265PTFE/10 |
| | |
| | |