



HIGH QUALITY EXTRACTION ARM

Durable extraction arms designed to provide best performance during extraction of fumes & dusts.

STATE OF THE ART EXTRACTION HOOD

Special designed extraction hood provide superior performance.

CLEANABLE CARTRIDGE FILTERS

Top quality and cleanable cartridge filters allow you long filter lifetime and lower cost of ownership

CONTROL & SIGNAL PANEL

Each device equipped with filter clog display, fan rotation direction display, ON/OFF switch and working hour counters.

GENERAL INFORMATION	
Filter Type	Cartridge
Filter Media	
Standard	nanoBLEND FR
Optional	polyMIGHT PTFE 65
No of Cartridge Filters	1
Total Filtration Area	
Standard	24 m ²
Optional	20 m ²
Filtration Efficiency	
Standard	F9 Class
Optional	H13/H14 Class

TECHNICAL INFORMATION	
Extraction Capacity	
1 Arm Model	1.400 m ³ /h
2 Arms Model	2 x 1.100 m ³ /h
Dimensions (W x L x H)	650 x 815 x 1.320 mm
Motor Power	1,1 kW - 3.000 rpm
Power Supply	380 V / 50 Hz
Noise Level	73 dB(a)

ORDER NO	
No Arm, SFS	TPRO.0.24.B135FR.50.380
1 Arm, 3 m, Inner Support, SFS	TPRO.131.24.B135FR.50.380
1 Arm, 3 m, External Support, SFS	TPRO.130.24.B135FR.50.380
1 Arm, 4 m, External Support, SFS	TPRO.140.24.B135FR.50.380
No Arm, OFS	TPRO.0.20.265PTFE.50.380
1 Arm, 3 m, Inner Support, OFS	TPRO.131.20.265PTFE.50.380
1 Arm, 3 m, External Support, OFS	TPRO.130.20.265PTFE.50.380
1 Arm, 4 m, External Support, OFS	TPRO.140.20.265PTFE.50.380
2 Arms, 3 m, Inner Support, SFS	TPRO.231.24.B135FR.50.380
2 Arms, 3 m, External Support, SFS	TPRO.230.24.B135FR.50.380
2 Arms, 4 m, External Support, SFS	TPRO.240.24.B135FR.50.380
2 Arms, 3 m, Inner Support, OFS	TPRO.231.20.265PTFE.50.380
2 Arms, 3 m, External Support, OFS	TPRO.230.20.265PTFE.50.380
2 Arms, 4 m, External Support, OFS	TPRO.240.20.265PTFE.50.380

SFS : Standard Filter Set
 OFS: Optional Filter Set

SPARE PART ORDER NO	
nanoBLEND FR Filter	HTM/380/660/B135FR/24
polyMIGHT PTFE 65 Filter	HTM/380/660/265PTFE/20
3 m Flexible Hose	MF-3H-S
4 m Flexible Hose	MF-4H-S