



**HIGH QUALITY EXTRACTION ARM**

Durable extraction arms designed to provide best performance during extraction of fumes & dusts.

**STATE OF THE ART EXTRACTION HOOD**

Special designed extraction hood provide superior performance.

**JET-PULSE AUTOMATIC CLEANING SYSTEM**

Automatic jet-pulse cleaning system for continuous operation and less frequent maintenance.

**CLEANABLE CARTRIDGE FILTERS**

Top quality and cleanable cartridge filters allow you long filter lifetime and lower cost of ownership

**CONTROL & SIGNAL PANEL**

Each device equipped with filter clog display, fan rotation direction display, ON/OFF switch and working hour counters.

GENERAL INFORMATION	
Filter Type	Cartridge
Filter Media	
Standard	nanoBLEND FR
Optional	polyMIGHT PTFE 65
No of Cartridge Filters	2
Total Filtration Area	
Standard	36 m <sup>2</sup>
Optional	20 m <sup>2</sup>
Filtration Efficiency	
Standard	F9 Class
Optional	H13/H14 Class

TECHNICAL INFORMATION	
Extraction Capacity	
1 Arm Model	1.400 m <sup>3</sup> /h
2 Arms Model	2 x 1.100 m <sup>3</sup> /h
Dimensions (W x L x H)	890 x 810 x 1.760 mm
Motor Power	1,1 kW - 3.000 rpm
Power Supply	380 V / 50 Hz
Noise Level	73 dB(a)

ORDER NO	
No Arm, SFS	TPULSE.0.36.B135FR.50.380
1 Arm, 3 m, Inner Support, SFS	TPULSE.131.36.B135FR.50.380
1 Arm, 3 m, External Support, SFS	TPULSE.130.36.B135FR.50.380
1 Arm, 4 m, External Support, SFS	TPULSE.140.36.B135FR.50.380
No Arm, OFS	TPULSE.0.20.265PTFE.50.380
1 Arm, 3 m, Inner Support, OFS	TPULSE.131.20.265PTFE.50.380
1 Arm, 3 m, External Support, OFS	TPULSE.130.20.265PTFE.50.380
1 Arm, 4 m, External Support, OFS	TPULSE.140.20.265PTFE.50.380
2 Arms, 3 m, Inner Support, SFS	TPULSE.231.36.B135FR.50.380
2 Arms, 3 m, External Support, SFS	TPULSE.230.36.B135FR.50.380
2 Arms, 4 m, External Support, SFS	TPULSE.240.36.B135FR.50.380
2 Arms, 3 m, Inner Support, OFS	TPULSE.231.20.265PTFE.50.380
2 Arms, 3 m, External Support, OFS	TPULSE.230.20.265PTFE.50.380
2 Arms, 4 m, External Support, OFS	TPULSE.240.20.265PTFE.50.380

SFS : Standard Filter Set  
 OFS: Optional Filter Set

SPARE PART ORDER NO	
nanoBLEND FR Filter	HTM/351/600/B135FR/18
polyMIGHT PTFE 65 Filter	HTM/351/600/265PTFE/10
3 m Flexible Hose	MF-3H-S
4 m Flexible Hose	MF-4H-S