



CLEANABLE CARTRIDGE FILTERS

Top quality and cleanable cartridge filters allow you long filter lifetime and lower cost of ownership

EXPANDABLE WORKING AREA

Openable side panels allow you to expand working area. 3 Position is available

INTEGRATED SPARK SHIELD

Integrated spark shield protect main dust collector from sparks which could be arise during grinding operation

INTEGRATED RADIAL FAN

High efficient and silent radial fan provides high extraction efficiency

TRAY FOR WASTE DUST

Tray for easy discharge of waste dust

GENERAL INFORMATION

Filter Type	Cartridge
Filter Media	
Standard	nanoBLEND FR
Optional	polyMIGHT PTFE 65
No of Cartridge Filters	2
Total Filtration Area	
Standard	40 m ²
Optional	20 m ²
Filtration Efficiency	
Standard	F9 Class
Optional	H13/H14 Class

TECHNICAL INFORMATION

Extraction Capacity	
Standard	2.500 m ³ /h
PRO version	5.500 m ³ /h
Dimensions (W x L x H)	1.300 x 1.100 x 1.450 mm
Motor Power	
Standard	1,5 kW - 1.500 rpm
PRO version	4,0 kW - 3.000 rpm
Power Supply	380 V / 50 Hz
Noise Level	75 dB(a)

ORDER NO

Standard Version, SFS	TBENCH.80.120.40.B135FR.380.50
Standard Version, OFS	TBENCH.80.120.20.265PTFE.380.50
PRO Version, SFS	TBENCHPRO.80.120.40.B135FR.380.50
PRO Version, OFS	TBENCHPRO.80.120.20.265PTFE.380.50

SFS : Standard Filter Set

OFS: Optional Filter Set

SPARE PART ORDER NO

nanoBLEND FR Filter	HTM/450/450/500/B135FR/20
polyMIGHT PTFE 65 Filter	HTM/450/450/500/265PTFE/10