



#### Overview

- High Quality and Durable Steel Structure
- 380 V & 460 V Options
- High Vacuum Power with Side Channel Blower
- Plug & Play

#### Standard Features

- Automatic Jet-Pulse Cleaning System
- Low Vacuum Alarm
- Can be equipped with AUTO START/STOP sensor
- Waste Dust Bin
- Long lifetime with brushless side channel blower

#### Applications

- On torch welding fume extraction
- Robotic welding process
- Direct vacuum from hand tools

#### Technical Data

##### Filter

Filter Stage	1
Filter Technology	Cleanable Cartridge Filter
Filter Media	
Standard	nanoBLEND FR
Optional	polyMIGHT PTFE 65
Filtration Area	
Standard	10 m <sup>2</sup>
Optional	20 m <sup>2</sup>
Filtration Eff.	
Standard	F9 (MERV 16) Class
Optional	H13 Class

##### Basic Information

Extraction Capacity	max.210 m <sup>3</sup> /h
Vacuum Pressure	max. 200 mBar
Dimension	600 x 885 x 1.100 mm
Weight	150kg
Motor Power	1,6 kW - 2.850 rpm
Power Supply	
Standard	380 V - 50 Hz
Optional	460 V - 60 Hz
Sound Level	<70 dB(a)

##### Additional Information

CE Certification	CE Certified
Fan Type	Side Channel Blower
Cleaning Type	Jet-Pulse
Dust Bin	25 Lt
Inlet Dimension	Ø50 mm
Thermal Value	3.5A
Nominal Current	3A
HS Code	8421.39.85.90.00

##### Boyutlar

