



HIGH QUALITY EXTRACTION ARM

Durable extraction arms designed to provide best performance during extraction of fumes & dusts.

STATE OF THE ART EXTRACTION HOOD

Special designed extraction hood provide superior performance.

CLEANABLE CARTRIDGE FILTERS

Top quality and cleanable cartridge filters allow you long filter lifetime and lower cost of ownership

CONTROL & SIGNAL PANEL

Each device equipped with filter clog display, fan rotation direction display, ON/OFF switch and working hour counters.

GENERAL INFORMATION

Filter Type	Cartridge
Filter Media	
Standard	nanoBLEND FR
Optional	polyMIGHT PTFE 65
No of Cartridge Filters	1
Total Filtration Area	
Standard	18 m ²
Optional	10 m ²
Filtration Efficiency	
Standard	F9 Class
Optional	H13/H14 Class

ORDER NO - FILTER UNIT

No Arm, SFS,230 V	TMONO.0.18.B135FR.50.230
No Arm, SFS,380 V	TMONO.0.18.B135FR.50.380
No Arm, OFS,230 V	TMONO.0.10.265PTFE.50.230
No Arm, OFS,380 V	TMONO.0.10.265PTFE.50.380

SFS : Standard Filter Set

OFS : Optional Filter Set

ORDER NO - ACCESSORIES

Extraction Arm, 2 mt, Inner Support	F.PRO.2.N
Extraction Arm, 3 mt, Inner Support	F.PRO.3.N
Extraction Arm, 3 mt, External Support	F.PLUS.3.N
Extraction Arm, 4 mt, External Support	F.PLUS.4.N

TECHNICAL INFORMATION

Extraction Capacity	1.200 m ³ /h
Dimensions (W x L x H)	660 x 805 x 1.210 mm
Motor Power	
Standard #1 [3-Phase]	0,75 kW - 3.000 rpm
Standar #2 [1-Phase]	1,10 kW - 3.000 rpm
Power Supply	
Standard #1 [3-Phase]	380 V / 50 Hz
Standar #2 [1-Phase]	230 V / 50 Hz
Noise Level	72 dB(a)

SPARE PART ORDER NO

nanoBLEND FR Filter (SFS Filter)	HTM/351/600/B135FR/18
polyMIGHT PTFE 65 Filter (OFS Filter)	HTM/351/600/265PTFE/10
Flexible Hose for 2 mt Arm	MF-2H-S
Flexible Hose for 3 mt Arm	MF-3H-S
Flexible Hose for 4 mt Arm	MF-4H-S